

RAINMAKER 810

Maximise your profits with a Water Reclaim System



KEY BENEFITS:

- Reduce your water bills
- Reduce your sewer output
- Reduce or even eliminate waste discharge fees
- Drought proof your operations
- Low operating expense
- Less tank pumping
- Easy maintenance procedures

MAINTENANCE

Maintenance on any equipment is essential to keep it running and ensure its longevity. We have ensured maintenance on your Reclaim 810 is minimal, easy to do and will leave you with no down time and protect the life of your valuable asset.

QUALITY

Powder coated aluminium frame (custom colours available)
Schedule 80 PVC plumbing
Stainless steel filter vessels
Complete instrumentation
Parts warranty available.

KEY FEATURES:

- Pressurised filter water drain (no mess)
- Self contained pre wired and pre plumbed
- Fully automated, one time set up
- Powerful, pressurised ozone system
- Provides clean, odour free water in a simple package
- Small footprint, so minimal space required
- Electronics are completely enclosed in water resistant enclosure
- Suction strainer basket provide additional protection for pumps from debris
- Disposable filter bags (1 to 25 microns)
- Low pressure safety switch prevents the pumps running dry.



RAINMAKER 810 GENERAL SYSTEM SPECIFICATION

Height	75"					
Width	80"					
Depth	30"					
Weight	800lb					
Frame	6061 Aluminium powder coated					
FILTRATION SYSTEM						
Input power	208/230/460/575 Volt, 3 Phase, 17.5- 15.2-7.6-6.1					
Control power	(below) 115 Volts @ 15 amp max					
On/ Off control	Switch selectable off/on					
Waste water inlet	2" or 3" pipe					
Primary pump	Five (5) HP, pmps up to 60/100 GPM at 60 PSI Max					
Inlet filtration	Strainer basket (stainless steel)					
Filtration vessels	Stainless steel or alum					
Primary Filtration	3 reuseable / Disposable bags (5 to 100 micron filters available)					
Filtered water outlet	1 ½" PVC					
Drain outlet	1 ½" PVC					
Optional	2" self cleaning filter					
OZONE RECIRCULATION SYSTEM						
Input power	208/230/480 Volt, 3 Phase @ 6.9-6.0-3.0-2.4 amp max					
Control power	115 Volts @ 15 amp max					
On/ Off control	Switch selectable On/ Off					
Waste water inlet	1 ½" PVC					
Recirculation pump	1.5 HP capable of pumping up to 30 GPM @ 40 PSI					
Inlet filtration	Strainer basket (stainless steel)					
Ozone injection:	Mazzi ozone generator					
Ozone Generator:	High efficiency Corona discharge providing 28 grams/hr					
Ozone water outlet:	1" PVC					
SUPPLY POWER						
Pump Voltage	200	208	230	400	460	575
	40	40	35	35	30	25
Control voltage Branch fuse rating amps: 1- phase @ 25 amps for 11 VAC.						

Fleetwash Industrial Systems Pty Ltd - ABN: 72 069 334 032

Manufacturers of the "Deluge" range of automatic truck washing systems, Distributors of the "Speedywash" mobile washing systems
 Deluge Sales & Manufacturing: 6A Longabardi St Dubbo NSW 2830 Tel: 02 6884 1919 Fax: 02 6884 1919
 Administration- Speedywash Sales & Service: 4/10 Tollis Place Seven Hills NSW 2147 Tel: 02 9620 9629 Fax: 02 9624 8763
 PO Box 7883 Baulkham Hills BC NSW 2153 Email . info@fleetwash.com.au Web. www.fleetwash.com.au